



SENTINEL

○ SENTINEL SENSORS

SENTINEL SENSORS



SMALL - SMART - SECURE

Sentinel is HSI Sensing's elite, **high-security** entry-point sensor. As a **UL 634 Level 2** listed sensor, Sentinel excels where failure is not an option, like government facilities, prisons, banks, weapon sites and other high-security areas. Sentinel's intelligent design **resists physical, electrical and magnetic tampering**. Smart algorithms allow the Hall sensors within Sentinel's aluminum body to deliver multiple unique output states. When reliable security is a priority, Sentinel is always standing guard.



SENTINEL SENSORS

SPECS

HIGH SECURITY. LOW PROFILE.

Air Gap Range: 0 to 3/16 inch (0-4.8 mm)

Lateral (left/right) Alignment for Secure: 3/16 inch (4.8 mm) typical

Door Opening Gap for Secure (Gap of Separation): $\pm 1/4$ to $\pm 1/2$ inch (6.35-12.7 mm)

Ambient Temperature Range: -31°F to +158°F (-35°C to +70°C)

Mounting Environment: Indoor or Outdoor, Ingress or Egress Door, Ferrous or Nonferrous Surfaces

Power: 4.5 to 25.2V DC, 20mA max



PRX+12210
Side-exit metal-jacketed cable



PRX+12220
Rear-exit cable





SENTINEL



3100 NORGE ROAD, CHICKASHA, OKLAHOMA 73018 | [PHONE 405.224.4046](tel:405.224.4046) | [FAX 405.224.9423](tel:405.224.9423)
HSISENSING.COM